

CATEYE PADRONE SMART

SMART COMPUTER CC-PA500B Quick Start

The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by CATEYE Co., Ltd. is under license. Other trademarks and trade names are those of their respective owners.

Pat. and Design Pat. Pending
Copyright © 2018 CATEYE Co., Ltd.
CCPA500B-180109 06660119513

This Quick Start manual is for users who do not have a smartphone.
本紙はスマートフォンをお持ちでないユーザーを対象にしたクイックスタートです。

SMARTPHONE + PADRONE SMART
http://www.cateye.com/manual/CC-PA500B/
CATEYE PADRONE SMART

* If you have a smartphone or would like more detailed information, refer to the online manual on our website.
※ スマートフォンをお使いの方や詳しい情報を知りたい方はオンラインマニュアルをご覧ください。

FR: Ce Guide de démarrage rapide est destiné aux utilisateurs ne possédant pas de smartphone.
* Si vous possédez un smartphone, ou si vous souhaitez obtenir des informations plus détaillées, veuillez consulter le manuel en ligne disponible sur notre site web.

DE: Diese Schnellstartanleitung wurde für Anwender ohne Smartphone geschrieben.
* Wenn Sie ein Smartphone besitzen oder detaillierter informiert werden möchten, schauen Sie bitte in die Online-Anleitung oder besuchen Sie unsere Internetseiten.

NL: Deze snelstartgids is voor gebruikers zonder smartphone.
* Als u een smartphone hebt, of meer informatie wilt, bekijk dan de online handleiding op onze website.

ES: Este manual de inicio rápido es para usuarios que no tengan smartphone.
* Si tienen un smartphone o desea información más detallada, consulte el manual online en nuestra Web.

IT: La presente guida introduttiva è per tutti gli utenti che non dispongono di smartphone.
* Se si dispone di smartphone o si necessitano ulteriori informazioni, consultare il manuale online sul nostro sito web.

繁: 本快速操作指南適用於非智能手機用戶。
※ 智能手機用戶以及想知道詳細使用方法的用戶，請參閱在線操作手冊。

簡: 本快速操作指南適用於非智能手機用戶。
※ 智能手機用戶以及想知道詳細使用方法的用戶，請參閱在線操作手冊。

SE: Denna snabbstartshandbok är för användare som inte har en smartphone.
* Om du har en smartphone eller vill få mer detaljerad information, se online manualen på vår webbplats.

This device complies with Part 15 of the FCC Rules and Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
L' appareil est conforme à la réglementation FCC, section 15 et Industrie Canada RSS standard exempts de licence (s). Son utilisation est soumise à deux conditions :
1. L' appareil ne doit pas provoquer d' interférences nuisibles, et
2. L' appareil doit supporter les interférences reçues, y compris les interférences empêchant son fonctionnement correct.

Modifications The FCC requires the user to be notified that any changes or modifications made to this device that are not expressly approved by CatEye Co., Ltd. may void the user's authority to operate the equipment.
NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:
Reorient or relocate the receiving antenna.
Increase the separation between the equipment and receiver.
Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
Consult the dealer or an experienced radio/TV technician for help.
This Class B digital apparatus complies with Canadian ICES-003.
Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.

Mounting the computer 自転車への取付方法

Computer コンピュータの着脱

Click

Stem or Handlebar ステム ハンドルバー

1 2 3 4

1 2 3 4

1 2 3 4

1 2 3 4

1 2 3 4

MODE button operation MODE ボタンの押し方

Press and release 普通に押す
Press and hold 長押し (2 sec.)

When installed on bracket ブラケット装着時

Click

AC MENU MODE

DOT section ドット部

Bluetooth® SMART Sensor 本器で使用できるセンサー

- Speed スピード
- Cadence ケイデンス
- Heart rate 心拍数
- Power パワー

OPTION (ISC-12)
1603970 Speed sensor (Speed/Cadence) スピードセンサー (スピード/ケイデンス)

OPTION (HR-12)
1603980 Heart rate sensor kit 心拍センサー

OPTION
Power sensor パワーセンサー

The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by CATEYE Co., Ltd. is under license. Other trademarks and trade names are those of their respective owners.

Setting up the computer コンピュータのセットアップ

1 Format フォーマット操作

MENU

Smartphone search screen スマホサーチ画面

2 km/h or mph 計測単位の選択

MENU

Skip スキップさせる

km/h ↔ m/h

3 Sensor ID ベアリング(センサー ID 照合)

Pair the computer with the sensor. 使用するセンサーをペアリングします。

Produce a sensor signal. センサー信号を発信させる

SENSOR ZONE (ISC-12)

Searching ID ID照合中

Type of sensor is automatically detected. センサー種別は自動判別します

- ISC Speed/Cadence スピード/ケイデンス
- SP Speed スピード
- CD Cadence ケイデンス
- HR Heart rate 心拍数
- P Power パワー

Repeat if you have other sensors. 別のセンサーがある場合は繰り返す

Pairing complete ベアリング完了

For details of pairing, refer to the online manual on our website. ベアリングの詳細については、オンラインマニュアルをご覧ください。

4 Tire size タイヤ周長の入力

When no speed sensor is paired, tire size entry is skipped. スピードセンサーのペアリングをしなかった場合、タイヤ周長入力はスキップします。

Tire size タイヤ周長ガイド

L = 100 - 3999 mm			Tire size			L (mm)		
47-203	12x1.75	935	28-590	26x1-1/8	1970			
54-203	12x1.95	940	37-590	26x1-3/8	2068			
40-254	14x1.50	1020	37-584	26x1-1/2	2100			
47-254	14x1.75	1055	650C Tubular 26x7/8 1920					
40-305	16x1.50	1185	20-571 650x20C 1938					
47-305	16x1.75	1195	23-571 650x23C 1944					
54-305	16x2.00	1245	25-571 650x25C 1952					
28-349	16x1-1/8	1290	40-590 650x38A 2125					
37-349	16x1-3/8	1300	40-584 650x38B 2105					
32-369	17x1-1/4(369)	1340	25-630 27x1(630) 2145					
40-355	18x1.50	1340	28-630 27x1-1/8 2155					
47-355	18x1.75	1350	32-630 27x1-1/4 2161					
32-406	20x1.25	1450	37-630 27x1-3/8 2169					
35-406	20x1.35	1460	40-584 27.5x1.50 2079					
40-406	20x1.50	1490	50-584 27.5x19.5 2090					
47-406	20x1.75	1515	54-584 27.5x2.1 2148					
50-406	20x1.95	1565	57-584 27.5x2.25 2182					
28-451	20x1-1/8	1545	18-622 700x18C 2070					
37-451	20x1-3/8	1615	19-622 700x19C 2080					
40-501	22x1-1/2	1785	20-622 700x20C 2086					
47-507	24x1.75	1890	23-622 700x23C 2096					
50-507	24x2.00	1925	25-622 700x25C 2105					
54-507	24x2.125	1965	28-622 700x28C 2136					
25-520	24x1(520)	1753	30-622 700x30C 2146					
			32-622 700x32C 2155					
			700C Tubular 2130					
28-540	24x1-1/8	1795	35-622 700x35C 2168					
32-540	24x1-1/4	1905	38-622 700x38C 2180					
25-559	26x1(559)	1913	40-622 700x40C 2200					
37-559	26x1.25	1950	42-622 700x42C 2224					
40-559	26x1.40	2005	44-622 700x44C 2235					
40-559	26x1.50	2010	45-622 700x45C 2242					
47-559	26x1.75	2023	47-622 700x47C 2268					
50-559	26x1.95	2050	54-622 29x2.1 2288					
54-559	26x2.10	2068	56-622 29x2.2 2298					
57-559	26x2.125	2070	60-622 29x2.3 2326					
58-559	26x2.35	2083						
75-559	26x3.00	2170						

Size of tire that sensor will be used with センサー装着側のタイヤ周長

5 Clock 時刻設定

24H/12H 24 ↔ 12

Only when 12H time is selected 12H 選択時のみ

AM/PM AM ↔ PM

Hour 時 0 - 23 [1 - 12]

Minutes 分 00 - 59

6 Finish セットアップの完了

Continued overleaf 裏面に続く

OPERATION FLOW

